



2*1000Base-X, 8*10/100/1000Base-T

Industrial Switch SWINASMM8GSFP



Input Voltage: DC10~58V

Operating Temperature: -30°C ~ +75°C

Shell: IP40 protection, fanless design

MTBF:100000 Hours

Anti-static: 8KV-15KV

Description.

The Ethernet switch uses store-forward architecture, fan-less and energy-saving design. Then design complies with the Ethernet standard with lightning and anti-static protection. They apply to the wide range of operating temperature from -30°C to +75°C with stable and reliable performance. They can be widely applied to various broadband data transmission fields, such as intelligent transportation, Telecommunications, security, financial securities, customs, shipping, power, water conservancy and oil fields.

**Specifications:**

Port	Fiber	2*1000 Base-X
	RJ45	8*10/100/1000 Base-T
	Power	Phoenix terminal blocks, redundant
Distance	Twisted-pair	0-100meter
	Single mode Optical Fiber	0~100km
	Multi-mode Optical Fiber	550m/2km
Fiber	Wavelength	Dual fiber 850nm, 1310nm, 1550nm Single fiber 1310/1550nm, 1490/1550nm
	Connector	SC(default)/FC/ST/LC
Networking	Star/Bus/Tree Topology	Support
	Scale	Non-limitation
Power	Input Voltage	DC10-58V
	Power Consumption	<5W
Layer 2	Switching Capacity	20G
	Packet Forwarding Rate	14.88Mpps
	MAC Address Table	16K
	Buffer	2M
	Forwarding Delay	<5us
	RJ45 Port	Twisted-pair, adaptive
	Jumbo Frame	10K bytes
	Traffic Control	Support
Mechanical Structure	Installation Method	Din-rail
	LED Indicator	PWR,Link/ACT
	Case	Fan-less, natural cooling
	Dimension	143*104*46mm
	Weight	0.54kg
Working Environment	Operating Temperature	-30°C~+75°C
	Storage Temperature	-40°C~+85°C
	Relative Humidity	5%~95% (non-condensing)
	MTBF	100,000 Hours



Protection Level	IP Level	IP40
	Power -Surge Protection	IEC 61000-4-5 Level 3 (4KV/2KV) (8/20us)
	Ethernet Surge Protection	IEC 61000-4-5 Level 3 (4KV/2KV) (10/700us)
	EMI	CLASS A
	ESD	IEC 61000--4-2 Level 4 (8K/15K)
	Free-drop	0.5meter
	Anti-static	8KV-15KV

Technical drawings

